FUNCTIONAL PRODUCTS INC.

Innovative Chemistry for Lubricants

Technical Data Sheet

FUNCTIONAL V-100

SUPERIOR SHEAR STABLE VISCOSITY INDEX IMPROVER IN BALE FORM

APPLICATION:

FUNCTIONAL V-100 is a viscosity index (V.I.) improver polymer supplied in bale form. It can be dissolved in oil to prepare an economical additive for multi-grade engine oils or an aftermarket "oil treatment" additive. It may also be used as an inexpensive thickener for oil to avoid blending with expensive oils like bright stocks.

COMPOSITION:

FUNCTIONAL V-100 is an olefin copolymer, derived from ethylene and propylene.

Typical Properties	
Appearance	White rubber
Specific Gravity:	0.87
Thickening efficiency	11 cSt at 100°C
(1.0% in ISO 32 oil)	
Shear Stability Index	22%
(PSSI) ASTM D6022	

TREATMENT LEVEL:

Treatment levels of 0.5-2.0% are typical in industrial lubricants and greases. The detergent-inhibitors used in formulating modern motor oils contain significant but varying levels of polymeric additives. The V.I. improver treatment level therefore depends on the choice of detergent package.

HANDLING:

FUNCTIONAL V-100 should be stored below about 120°F (50°C). It is a non-hazardous material; see the current Safety Data Sheet. Dissolving is best accomplished with continuous agitation at temperatures of 180-210°F (85-100°C). (Higher temperatures will not affect **FUNCTIONAL V-100** but may darken the diluent oil.)

This Technical Data Sheet and the Safety Data Sheet contain information believed to be accurate and reliable. No warranty is made, however, to information beyond the control of FUNCTIONAL PRODUCTS INC. The engineering and management personnel of the user are responsible for determining the suitability of this or any product for any specific application, and this information is offered to them for that purpose.

Issued: 10/14/2013