

www.functionalproducts.com

Treat/wt%		Light Color	Low Odor	Ecolabel/LuSC	MIL-PRF-32073	Paraffinic Oil			Ester					PAG		
						Group I	Group II	Group III	PAO / mPAO	Naphthenic Oil	Vegetable Oil	TMP Unsat.	TMP Sat.	Adipate	Oil Soluble	Water Soluble
Gear Oil Additives																
GA-604	1.85%	•	•			•	•	•	•	•	•	•	•	•	•	•
GA-614	1.5-5.0%	•	•			•	•	•	•	•	•	•	•	•	•	•
Hydraulic Fluid Additives																
HF-560	1.90%				•					•	•	•	•	•	•	•
HF-580	2.50%	•	•			•	•	•	•	•	•	•	•	•		•
HF-590	5.40%	•	•	•		•	•	•	•	•	•	•	•	•	•	•
Way Oil Additives																
WA-24	2.00%					•				•	•	•	•	•		
WA-64	1.75%	•	•			•	•	•	•	•	•	•	•	•		•
WA-60SF	1.50%	•	•			•	•	•	•	•	•	•	•	•		•
Rock Drill Oil Additives																
RD-535	6.00%	•				•				•	•	•	•	•	•	
RD-535CP	6.00%	•				•	•	•		•	•	•	•	•	•	
Saw Guide Oil Additives																
SGP-567	1.50%	•	•			•	•	•	•	•	•	•	•	•	•	•
SGP-571	3.00%	•	•	•		•	•	•	•	•	•	•	•	•	•	•

Compatible = clear and bright solution at treat (min. 5wt%) after freeze/thaw