

Tackifiers		Typical Viscosity cSt @ 100C	Treat Level wt %									
V-176	Versatile PIB tackifier for all applications in industrial lubricants and greases.	3,000	0.5 – 2	●	●	●						
V-178	High strength, efficient PIB tackifier best suited for machining oils and slideway lubricants.	4,000	0.5 – 2	●	●	●				●		
V-177	Concentrated heavy duty PIB tackifier specialized for greases, coatings, and rust preventatives.	10,500	0.5 – 2	●	●	●				●		
V-298	Clear and colorless PIB tackifier for textile oils or other lubricants that require no color/staining.	4,000	0.5 – 2	●	●	●				●		
PARATAC	Legacy PIB tackifier with long-standing OEM approvals.	3,000	0.5 – 2	●	●	●	●			●		
V-188	Specialty OCP tackifier for increased shear and thermal stability in gear oil. NSF HX-1 and Ecolabel versions available.	4,000	0.5 – 2	●	●	●	●			●	●	●
V-422	Incidental food contact PIB tackifier for NSF H1 lubricants and greases.	3,000	0.5 – 2	●	●	●	●			●	●	
V-584	Unique bio tackifier for vegetable oil and esters. NSF HX-1 and Ecolabel LuSC.	2,500@40°C	3 – 10	●	●	●	●			●	●	●
V-802P	Aqueous tackifier for water and emulsion lubricants. Compatible in certain glycol or PAG.	40,000@40°C	0.3 – 5	●	●	●	●			●	●	
V-870	Clear and colorless tackifier and anti-mist agent for silicone oils, lubes, and greases.	8,500	0.2 – 4	●	●	●	●			●	●	

Viscosity Modifiers & Base Stocks		Shear Stability Index (SSI)	Thickening Efficiency in ISO 32, cSt @ 100C	Typical Viscosity cSt @ 100C	Treat Level wt %								
V-158F	Liquid OCP viscosity modifier. V-158FN in naphthenic, V-158P2 in PAO.	50	10% = 12.5	1,600	5 – 10	●	●	●					
V-166	Liquid OCP viscosity modifier.	35	10% = 11.4	1,200	5 – 10	●	●	●					
V-160F	Liquid OCP viscosity modifier. V-460 for NSF HX-1. V-160P2 in PAO.	22	10% = 13.7	3,000	5 – 10	●	●	●				●	
V-705	High performance low temp base stock for VHVI HF. (KRL shear loss = 4%)	0	10% = 20.3	6,500	2 – 20	●	●	●	●		●	●	
V-515	Liquid bio viscosity modifier for vegetable oil and PAO/ester blends. Slight tack.	50	10% = 12.0	8,000	5 – 15	●	●	●	●		●	●	●
V-521	Liquid bio viscosity modifier for vegetable oil, esters. Exceptional low temperature flow.	30	10% = 16.4	5,000	5 – 15	●	●	●	●		●	●	●
V-508F	Liquid bio viscosity modifier for vegetable oil, esters. Widest compatibility in esters.	28	10% = 22.9	7,000	5 – 15	●	●	●	●		●	●	●
MH-4500	PMA viscosity modifier for general use (KRL shear loss = 65%)	15	10% = 12.3	1,500	5 – 20	●	●	●	●		●	●	●
MH-2000	PMA viscosity modifier for industrial hydraulic oils (KRL shear loss = 35%)	1	10% = 11.1	1,000	5 – 20	●	●	●	●		●	●	●
MB-1010	PMA base stock for gear oils and full synthetic lubes (KRL shear loss = 15%)	0	10% = 8.6	900	5 – 20	●	●	●	●		●	●	●
V-201	Pellet form OCP viscosity modifier, highly efficient. 5.4wt% = 1000 cSt @ 100°C	60	1% = 21.0	Pellet	0.5 – 2	●	●	●	●		●	●	●
V-255	Pellet form shear stable OCP viscosity modifier. 12% = 1000 cSt @ 100°C	25	1% = 10.5	Pellet	0.5 – 2	●	●	●	●		●	●	●
V-820	Water soluble powder to thicken water-based lubricants, emulsions.	N/A	0.5% = ISO 100	Powder	0.1 – 2	●	●	●	●		●	●	●

Grease Additives		Treat Level wt %								
V-207	Powder polymer for water resistance, shear stability, and tack. Best for calcium and aluminum greases. V-211 for NSF HX-1.	0.5 – 2	●	●						●
V-4020	Reactive pellet polymer to improve water resistance. Best for lithium and lithium complex greases.	0.2 – 1	●	●						
V-4004A	Pre-dissolved liquid reactive grease polymer; Ecolabel LuSC options available.	3 – 5	●	●					●	●
V-191	Polymer emulsion stable against water during and after production. Improved water spray-off and tack. Best for clay or silica greases.	0.5 – 2	●	●					●	●
V-4700	Liquid polymer for improving water resistance of synthetic-based greases (mPAO, PB, etc.) which don't respond to other options.	1 – 5	●	●					●	
V-4055	Concentrated viscosity modifier to replace heavy synthetic base stocks (mPAO) and improve water resistance, yield, adhesion, and tack.	5 – 10	●	●					●	

Specialty Packages & Additives		Treat Level wt %								
CI-426	Corrosion inhibitor and anti-wear additive for HX-1. CI-427 for low color and wide read-across. CI-426EP for improved EP.	0.5 – 2	●	●	●	●	●	●	●	●
GA-307	Economical zinc-free gear oil package with excellent corrosion resistance. GA-614 for top tier ashless gear. GA-400 for NSF HX-1.	3 – 8	●	●	●	●	●	●	●	●
HF-595	Biobased ashless AW hydraulic fluid package; Ecolabel LuSC. HF-580 for top tier ashless industrial HF, variable treat.	2.2	●	●	●	●	●	●	●	●
RD-540	Biobased rock drill, air tool, and open gear package; emulsifying. RD-540CP for demulsifying.	2.2	●	●	●	●	●	●	●	●
WA-64	Light color, low odor, compatible in a range of base oils. Cincinnati Fives stick-slip test. WA-60SF for colorless sulfur-free way oils.	1.75	●	●	●	●	●	●	●	●
SGP-563	Low friction AW/R&O package for saw/chain/forestry; reduced operating temperatures; Ecolabel LuSC. SGP-567 for more AW/EP.	1.5	●	●	●	●	●	●	●	●
V-162	Anti-mist additive for petroleum oils and does not add tackiness. Use MW-612 for aqueous or oil-water fluids.	0.02 – 0.1	●	●	●	●	●	●	●	●
DF-500	Defoamer for veg oil, fatty esters; Ecolabel LuSC. DF-400 is NSF HX-1 and Ecolabel LuSC for petroleum/ester. DF-110 for Gr. III and IV.	0.05 – 0.5	●	●	●	●	●	●	●	●
PD-585	Pour point depressant for vegetable oil; Ecolabel LuSC, US EPA Safer Choice. PD-590 for low viscosity. PD-571 economy biobased PPD.	0.1 – 1	●	●	●	●	●	●	●	●
PD-620	Pour point depressant for light Gr. I/II paraffinic oils. PD-610 for medium to heavy Gr. I/II oils. PD-630 for Gr. III oils.	0.1 – 0.5	●	●	●	●	●	●	●	●

Purchasing Information

Headquarters

Functional Products Inc.

8282 Bavaria Road
Macedonia, OH 44056
Phone: 330-963-3060
Fax: 330-963-3322
sales@functionalproducts.com
www.functionalproducts.com

North America

USA - Midwest / Gulf Coast

Hall Technologies

St. Louis, MO
Phone: 314-725-2600
www.halltechinc.com

USA - East Coast

Van Horn, Metz & Co.

Conshohocken, PA
Phone: 610-828-4500
marketing@vanhornmetz.com
www.vanhornmetz.com

USA - West Coast

Tri-Iso Tryline, LLC

Del Mar, CA
Phone: 909-626-4855
www.tri-iso.com

Canada

IMCD Canada Limited

Brampton, Ontario
Phone: 800-575-3382
www.imcdca.com

Mexico

Proaindsa

Mexico City DF, Mexico
Phone: 011-52-555-696-5551
jgarduno@proaindsa.com

Europe

France

Lumar France

Carrières sur Seine, France
Phone: +33 (0) 1 80 83 50 40
contact@lumarfrance.com
www.lumarfrance.com

Germany / Switzerland / Austria

Krahn Chemie Deutschland GmbH

Hamburg, Germany
Phone: +49 40 32092-0
info.de@krahn.eu

Italy

Lumar Italia Srl

Assago, Italy
informazioni@lumaritalia.com
www.lumaritalia.com

Poland / Hungary / Baltics / Czech Rep. / Slovakia / Ukraine

Krahn UK Limited

Cheshire, UK
Phone: +44 (0)1270 759128
uk.sales@krahn.eu

Scandinavia / Iceland

Krahn Nordics

Hisings Backa, Sweden
Phone: +46 31 775 67 80
anders.malmstroem@krahn.eu
www.krahn nordics.com

Spain / Portugal / Turkey / Greece

Lumar Quimica, S.L.U.

Barcelona, Spain
lumar@lumarquimica.com
www.lumarquimica.com

United Kingdom

Lumar UK

London, England
Phone: 0203 318 5697

Asia

China

Greenbase Industries, Inc.

Shanghai
Phone: 86-186-2158-0862

Smart Oil & Chemical Limited

Hong Kong
www.smart-oil.com

India / Bangladesh

Environ Specialty Chemicals Pvt. Ltd.

Mumbai, India
Phone: +91-22-42489200/230
sales@environchem.com
www.envirochem.com

Japan

Nippon Chemical Sales Co., Ltd.

Tokyo, Japan
Phone: 03-3719-0366
terui@ncstokyo.co.jp
info@ncstokyo.co.jp

Korea

Inwoo Corp.

Gyeonggi-do, Republic of Korea
Phone: 82-2-2202-7028
inwoo@inwoocorp.co.kr
www.inwoocorp.co.kr

Southeast Asia

Ewaka International Pte. Ltd.

Singapore
Phone: 65-6348-7279
rianto@ewekainternational.com.sg
www.ewekainternational.com.sg

Taiwan, ROC

Shiony Chemical Co. Ltd.

Taipei
Phone: 886-2-2356-0258
shiony@ms31.hinet.net
shiony.taipei@msa.hinet.net
www.shiony.com

Australia

Australia

IMCD Australia Limited

Mulgrave, Australia
Phone: 61-3-8544-3100
cs@imcd.com.au
www.imcdgroup.com

Central / South America

Central / South America

DNL Chemical

Phone: 800-726-0311
ToddC@DNLChemical.com
www.DNLChemical.com

Middle East

United Arab Emirates

Environ Specialty

Chemicals Gulf FZE

Ras Al Khaimah, UAE
Phone: +971 52548 5751
ravi@environchemfze.com