

FUNCTIONAL V-736

INDUSTRIAL ETHYLENE-PROPYLENE OLIGOMER (EPO) – 600 cSt

APPLICATION:

FUNCTIONAL V-736 is a pure liquid viscosity modifier and synthetic base stock with high thickening efficiency, excellent shear stability, and low temperature fluidity for high performance at lower cost per treat. **FUNCTIONAL V-736** is effective in high VI hydraulic fluids, industrial gear oils, automotive gear oils (75W), and grease.

COMPOSITION:

FUNCTIONAL V-736 is a liquid, low molecular weight ethylene-propylene copolymer with no diluent.

| Typical Properties | |
|--|---|
| Appearance, Visual | Clear to Slight Haze Slight Yellow to Yellow |
| Color, ASTM D1500 | 1.0 |
| Kinematic Viscosity, ASTM D445 | 550 cSt @ 100°C 9,000 cSt @ 40°C |
| Viscosity Index, ASTM D2270 | 235 |
| Density (lb/gal), ASTM D1475 | 7.1 lb/gal |
| Density (g/mL) @ 20°C/68°F | 0.85 g/mL |
| Flash Point, ASTM D92 COC | 280°C (536°F) |
| Thickening Efficiency, 10wt% in ISO 32 Group I | 10.8 cSt @ 100°C |
| Shear Stability Index (PSSI), ASTM D6278 | 0 SSI |
| 20hr KRL Shear Stability, CEC L-45-A-99 | 4.5 SSI |

TREATMENT LEVEL:

Treatment levels of 2 – 30% are typical in industrial lubricants and greases. **FUNCTIONAL V-736** can be used as either a VI improver or a shear stable base stock depending on the need. **FUNCTIONAL V-736** is compatible in most petroleum oils, synthetic oils, PAO, and esters.

Full synthetic formulas using EPO viscosity modifiers may require 5-10wt% ester for solubility.

HANDLING:

Dissolving is best accomplished with continuous agitation at temperatures of 104-140°F (40-60°C). **FUNCTIONAL V-736** may be preheated in a hot room or tank at up to 176°F (80°C) to aid in pumping but long term storage should remain below 140°F (60°C).

FUNCTIONAL V-736 is a non-hazardous material; see the current Safety Data Sheet.

This Technical Data Sheet and the Safety Data Sheet contain information believed to be accurate and reliable. No warranty is made, however, to information beyond the control of FUNCTIONAL PRODUCTS INC. The engineering and management personnel of the user are responsible for determining the suitability of this or any product for any specific application, and this information is offered to them for that purpose.

Version: 2023.06.27

Functional Products, Inc. 8282 Bavaria Rd. Macedonia, OH 44056

Ph: 330.963.3060 Fax:330.963.3322