

Tackifiers		Treat Level wt %											
V-176	Versatile PIB tackifier for all applications in industrial lubricants and greases.	0.5 – 2	●	●	●								
V-178	High strength, efficient PIB tackifier best suited for machining oils and slideway lubricants.	0.5 – 2	●	●	●								
V-177	Concentrated heavy duty PIB tackifier specialized for greases, coatings, and rust preventatives.	0.5 – 2	●	●	●								
V-298	Clear and colorless PIB tackifier for textile oils or other lubricants that require no color/staining.	0.5 – 2	●	●	●								
PARATAC	Legacy PIB tackifier with long-standing OEM approvals.	0.5 – 2	●	●	●	●							
V-188	Specialty OCP tackifier for increased shear and thermal stability in gear oil. NSF HX-1 and Ecocert available.	0.5 – 2	●	●	●	●							
V-422	Incidental food contact PIB tackifier for NSF H1 lubricants and greases.	0.5 – 2	●	●	●	●							
V-584	Unique bio tackifier for vegetable oil and esters; NSF HX-1 and Ecocert LuSC available.	3 – 10	●	●	●	●							
V-802	Aqueous tackifier for water and emulsion lubricants. NSF HX-1.	0.3 – 5				●							

Viscosity Modifiers (VM) & Base Stocks		Shear Stability Index (PSSI)	Polymer Chemistry	Thickening Eff. cSt @ 100C	Treat Level wt %									
V-158FN	Economic naphthenic viscosity modifier. V-158F for paraffinic Group II oil.	50	OCP	10% = 11.7	5 – 10	●	●	●						
V-166	Liquid OCP viscosity modifier. Lower cost V-166B in Group I and V-166N in naphthenic.	35	OCP	10% = 11.4	5 – 10	●	●			●	●			
V-160	Liquid OCP viscosity modifier. V-460 for NSF HX-1.	22	OCP	10% = 11.0	5 – 10	●	●			●	●	●		
V-4314	Liquid shear styrene olefin copolymer, 20-25 SSI.	23	Styrene OCP	10% = 12.3	10 – 20	●	●	●		●	●			
V-4312	Liquid shear stable styrene olefin copolymer, 5-10 SSI.	7	Styrene OCP	10% = 10.0	10 – 20	●	●			●	●			
V-4318	Liquid shear stable styrene olefin copolymer, 0-5 SSI.	3	Styrene OCP	10% = 8.9	10 – 20	●	●			●	●			
V-731	Liquid ethylene-propylene oligomer base stock. (15% KRL shear)	0	Polyolefin	10% = 12.1	5 – 10	●	●		●	●		●	●	●
V-705	Low temperature polyolefin base stock for VHVI HF. (4% KRL shear)	0	Polyolefin	10% = 20.3	5 – 10	●	●		●	●		●	●	●
V-515	Liquid bio VM for vegetable oil and PAO/ester blends. Best economics for chain and saw oils.	50	Biobased	10% = 12.0	5 – 10		●	●				●	●	●
V-521	Liquid bio VM for vegetable oil, esters. Best low temp fluidity for low pour point hydraulics.	30	Biobased	10% = 16.4	5 – 10		●	●		●	●	●	●	●
V-508M	Liquid bio VM for vegetable oil, esters. Best thermal stability for high temp esters. NSF HX-1.	28	Biobased	10% = 18.4	5 – 10		●	●		●	●	●	●	●
MD-8004	Dispersant PMA viscosity modifier for tractor, ATF. MD-2200 for 3 SSI.	40	D-PMA	10% = 16.9	5 – 20	●	●			●	●			
MH-2000	PMA viscosity modifier for industrial hydraulic oils (35% KRL shear)	1	PMA	10% = 11.1	5 – 20	●	●		●	●				
MB-1010	PMA base stock for gear oils and full synthetic lubes (15% KRL shear)	0	PMA	10% = 8.6	5 – 20	●	●		●	●				

Grease Additives		Recommended For:	Treat Level wt %										
V-207	Flake polymer for water resist., oil bleed, shear stability, and tack. V-211 for NSF HX-1.	Ca / Al	0.5 – 2	●	●								●
V-4020	Low treat reactive pellet to improve water resistance. V-4040P for faster dissolving colorless flake.	Li	0.2 – 0.5	●									
V-4004A	Pre-dissolved liquid reactive polymer for fast and complete addition to grease.	Li	3 – 5	●									
V-4700	Liquid reactive polymer for improving synthetic-based greases with low solvency.	Li / Ca	1 – 5	●								●	
V-191	Concentrated polymer emulsion to improve water spray-off, oil bleed, and tack.	Clay / Silica	0.5 – 2	●								●	●
V-4316	High SSI liquid styrene copolymer for water resistance, oil bleed, and tack in polyurea grease. V-4311 for low SSI.	Polyurea	5 – 10	●	●	●		●	●	●			

Specialty Packages & Additives		Application	Treat Level wt %										
CI-426	Amine phosphate antiwear / corrosion inhibitor, NSF HX-1. AW-116 for lower hazard, higher phosphorus option.	Antiwear	0.5 – 2	●	●	●	●	●	●	●	●	●	●
DM-240	Excellent demulsifier for petroleum oil lubricants. DM-400 for Ecocert and NSF HX-1.	Demulsibility	0.1 – 1	●		●	●	●	●	●	●	●	●
GA-614	Active sulfur and phosphorus GL-5 / US Steel / AGMA gear oil package. GA-400 for NSF H1. GA-533 for Ecocert.	Gear	2 – 6	●	●	●	●	●			●	●	●
HF-595	Ecocert biobased HF package (2.2wt%). HF-580 for biodegradable industrial HF (1.5 - 2.5wt%).	Hydraulic	2.2	●		●	●	●			●	●	●
PD-620	Pour point depressant for low visc. Group I/II. PD-610 for high visc. PD-630 for Gr. III oils. PD-585 for Ecocert.	Low Temp.	0.1 – 1.0	●	●	●	●	●	●	●	●	●	●
RD-350	Emulsifying EP rock drill, pneumatic oil, and air tool package for petroleum oils. RD-540 for vegetable oils.	Rock Drill	1.8	●	●	●	●	●			●	●	●
SGP-567	Multipurpose forestry and saw guide oil package. SGP-563 for Ecocert listed forestry oils.	Saw Guide	1.5	●		●					●	●	●
WA-64	Modern low color/odor way oil technology. Stick-slip pass. WA-60SF for colorless sulfur-free way oils.	Way Oil	1.75	●		●	●	●			●	●	●

FUNCTIONAL Sales and Distribution Network

Headquarters

Functional Products Inc.

8282 Bavaria Road
Macedonia, OH 44056
Phone: 330-963-3060
Fax: 330-963-3322
sales@functionalproducts.com
www.functionalproducts.com

North America

USA - Midwest

Omya Specialty Materials
St. Louis, MO
Phone: 314-725-2600
www.omya.com

USA - East Coast

Van Horn, Metz & Co.
Conshohocken, PA
Phone: 610-828-4500
marketing@vanhornmetz.com
www.vanhornmetz.com

USA - West Coast

Tri-Iso Tryline, LLC
Del Mar, CA
Phone: 909-626-4855
www.tri-iso.com

Canada

IMCD Canada Limited
Brampton, Ontario
Phone: 800-575-3382
www.imcdca.com

Mexico

Proaindsa
Mexico City DF, Mexico
Phone: 011-52-555-696-5551
jgarduno@proaindsa.com

Europe

France

LUMAR France
Carrières sur Seine, France
Phone: +33 (0) 1 80 83 50 40
contact@lumarfrance.com
www.lumarfrance.com

Germany

LUMAR Germany
Stuttgart, Germany
info@lumardeutschland.com
www.lumardeutschland.com

Italy

LUMAR Italia Srl
Assago, Italy
informazioni@lumaritalia.com
www.lumaritalia.com

Scandinavia / Iceland

Krahn Nordics
Hisings Backa, Sweden
Phone: +46 31 775 67 80
anders.malmstroem@krahn.eu
www.krahn nordics.com

Spain / Portugal / Turkey / Greece

Lumar Quimica, S.L.U.
Barcelona, Catalonia
Phone: + 34 93 594 75 00
lumar@lumarquimica.com
www.lumarquimica.com

United Kingdom

Lumar UK
London, England
Phone: 0203 318 5697
contact@lumar-uk.com
www.lumar-uk.com

Asia

China

Greenbase Industries, Inc.
Shanghai
Phone: 86-186-2158-0862

Smart Oil & Chemical Limited

Hong Kong
www.smart-oil.com

India / Bangladesh

Environ Specialty Chemicals Pvt. Ltd.
Mumbai, India
Phone: +91-22-42489200/230
sales@environchem.com
www.envirochem.com

Japan

Nippon Chemical Sales Co., Ltd.
Tokyo, Japan
Phone: 03-3719-0366
info@ncstokyo.co.jp

Korea

Inwoo Corp.
Gyeonggi-do, Republic of Korea
Phone: 82-2-2202-7028
inwoo@inwoocorp.co.kr
www.inwoocorp.co.kr

Southeast Asia

Ewaka International Pte. Ltd.
Singapore
Phone: 65-6348-7279
rianto@ewekainternational.com.sg
www.ewekainternational.com.sg

Taiwan, ROC

Shiony Chemical Co. Ltd.
Taipei
Phone: 886-2-2356-0258
shiony@ms31.hinet.net
shiony.taipei@msa.hinet.net
www.shiony.com

Australia

Australia

IMCD Australia Limited
Mulgrave, Australia
Phone: 61-3-8544-3100
cs@imcd.com.au
www.imcdgroup.com

Central/ South Americas

Central / South America

DNL Chemical
Phone: 800-726-0311
ToddC@DNLChemical.com
www.DNLChemical.com

Middle East

United Arab Emirates

**Environ Specialty
Chemicals Gulf FZE**
Ras Al Khaimah, UAE
Phone: +971 52548 5751
ravi@environchemfze.com
www.environchemfze.com

Africa

Northern Africa

Lumar Quimica, S.L.U.
Phone: + 34 93 594 75 00
lumar@lumarquimica.com
www.lumarquimica.com

South Africa

Azelis South Africa
Umhlanga Ridge
Phone: +27(31)5368297
info@umongo.co.za
www.umongo.co.za