

FUNCTIONAL V-166B

VISCOSITY INDEX IMPROVER

APPLICATION:

FUNCTIONAL V-166B is a viscosity index (V.I.) improver that may be used in preparing multi-grade engine oils as well as industrial fluids and lubricants. It may also be used without dilution as a supplemental crankcase additive for the automotive aftermarket.

COMPOSITION:

The active thickener in **FUNCTIONAL V-166B** is a copolymer of ethylene and propylene that has been used as a V.I. improver by major oil companies. The diluent in **FUNCTIONAL V-166B** is a light Group I oil.

Typical Properties	
Specific Gravity (15C)	0.86
Lbs per Gallon (23C)	7.2
Flash Point	160°C (320°F)
Kinematic Viscosity	1200 cSt at 100°C
Color	Yellow (1 - 3 ASTM)
PSSI (ASTM D6278, 30 cycles)	35%

TREATMENT LEVEL:

Treatment levels from 5 - 20% are typical in industrial lubricants and greases. Please refer to the application bulletins for more information.

HANDLING:

Due to the viscosity of **FUNCTIONAL V-166B**, elevated temperature (up to approximately 90°C or 200°F) can facilitate handling. Safe handling precautions are the same as those to be taken with the base oil; see the current Safety Data Sheet.

This Technical Data Sheet and the Safety Data Sheet contain information believed to be accurate and reliable. No warranty is made, however, to information beyond the control of FUNCTIONAL PRODUCTS INC. The engineering and management personnel of the user are responsible for determining the suitability of this or any product for any specific application, and this information is offered to them for that purpose.

Issue Date: 2018.04.24

Functional Products, Inc. 8282 Bavaria Rd. Macedonia, Ohio 44056

Ph: 330.963.3060 Fax: 330.963.3322